

## [2017-Aug.-UpdatedFull Version 300-101 Dumps PDF 470Q for Free Download[423-434

2017 Aug New 300-101 Exam Dumps with PDF and VCE Updated Today! Following are some new questions: 1.|2017 New 300-101 Exam Dumps (PDF & VCE) 470Q&As Download:<https://www.braindump2go.com/300-101.html> 2.|2017 New 300-101 Exam Questions & Answers Download:<https://drive.google.com/drive/folders/0B75b5xYLjSSNUIpIeEc2YV9vRDg?usp=sharing>

QUESTION 423 Which two methods use IPsec to provide secure connectivity from the branch office to the headquarters office? (Choose two.)

- A. DMVPN
- B. MPLS VPNC. Virtual Tunnel Interface (VTI)
- D. SSL VPNE. PPPoE

Answer: AC

QUESTION 424 Which two statements about Frame Relay Point-to-Point connections are true? (Choose Two)

- A. Changing a point-to-point sub interface to a different type requires the device to be reloaded.
- B. They use two DLCIs to communicate with multiple endpoints over the Frame Relay cloud.
- C. The device can establish a point-to-point connection to the cloud without a DLCI.
- D. They can operate normally without a DLCI map.
- E. Each physical interface that extends to the Frame Relay cloud can support a single SVC.

Answer: AB

QUESTION 425 What is the international standard for transmitting data over a cable system?

- A. PPPoE
- B. DOCSISC
- C. MTSD
- D. AAL5

Answer: B

QUESTION 426 Which interface type does a PPPoE client use to establish a session?

- A. Physical
- B. loopback
- C. visual-template
- D. dialer

Answer: D

Explanation:

<http://www.cisco.com/c/en/us/td/docs/ios/xml/ios/bbdsi/configuration/xe-3s/bba-pppoe-client.html>

QUESTION 427 The Cisco SA 500 Series Security Appliances are built specifically for businesses with less than 100 employees. What are three important benefits of this device? (Choose three)

- A. business-grade firewall
- B. premium support via SMART net
- C. site-to-site VPN for remote offices
- D. Cisco IOS software-based
- E. email security
- F. XML support

Answer: ACE

QUESTION 428 Which Cisco Express Forwarding component maintains Layer 2 addressing information?

- A. dCEF
- B. adjacency table
- C. FIB
- D. fast switching

Answer: B

Explanation: Adjacency Tables

Nodes in the network are said to be adjacent if they can reach each other with a single hop across a link layer. In addition to the FIB, CEF uses adjacency tables to prepend Layer 2 addressing information. The adjacency table maintains Layer 2 next-hop addresses for all FIB entries.

[http://www.cisco.com/c/en/us/td/docs/ios/12\\_2/switch/configuration/guide/fswtch\\_c/xcef.ht](http://www.cisco.com/c/en/us/td/docs/ios/12_2/switch/configuration/guide/fswtch_c/xcef.ht)

ml

QUESTION 430 Which two debug commands can you use to view issues with CHAP and PAP authentication? (Choose Two)

- A. debug tacacs
- B. debug ppp authentication
- C. debug radius
- D. debug aaa authentication
- E. debug ppp negotiation

Answer: BE

Explanation:

<http://www.cisco.com/c/en/us/support/docs/wan/point-to-point-protocol-ppp/25647-understanding-ppp-chap.html>

QUESTION 431 Which DSL encapsulation method requires client software running on the end-user PC that is directly connected to a DSL modem?

A. PPPoA

B. PPPoE

C. PPPoD

D. ATM

Answer: B

QUESTION 432 By default, which type of IPv6 address is used to build the EUI-64 bit format?

- A. unique-local address
- B. IPv4-compatible IPv6 address
- C. link-local address
- D. aggregatable-local address

Answer: C

Explanation: <https://howdoesinternetwork.com/2013/slaac-ipv6-stateless-address-autoconfiguration>

QUESTION 433 For a GRE tunnel to be up between two routers, which of the following must be configured?

- A. Loopback Interface
- B. IP reachability between the loopback interfaces
- C. Dynamic Routing between routers
- D. Tunnel interfaces must be in the same subnet

Answer: D

QUESTION 434 Which two statements about configuring Frame Relay point-to-multipoint connections are true? (Choose two)

- A. They ignore the broadcast keyword in the frame-relay DLCI mapping.
- B. They require the same DLCI on each side of the link.
- C. Changing a point-to-multipoint subinterface to a different type requires the interface to be deleted and recreated.
- D. They require the frame-relay mapping command to be configured.
- E. They require inverse ARP.

Answer: DE

!!!RECOMMEND!!!

1.|2017 New 300-101 Exam Dumps (PDF & VCE) 470Q&As Download:<https://www.braindump2go.com/300-101.html>

2.|2017 New 300-101 Study Guide Video: YouTube Video: [YouTube.com/watch?v=z16xR3aE6Yo](https://www.youtube.com/watch?v=z16xR3aE6Yo)