

[2017-July-NewsBraindump2go 200-150 Exam VCE Dumps Instant Download[11-20

2017 July CCNA 200-150 Exam Dumps with PDF and VCE New Updated in www.Braindump2go.com Today! 1.|2017 New 200-150 Exam Dumps (PDF & VCE) [106Q&As](#) Download:<http://www.Braindump2go.com/200-150.html> 2.|2017 New 200-150 Exam Questions & Answers Download:

<https://drive.google.com/drive/folders/0B75b5xYLjSSNVmxoUEhTTmZZMXc?usp=sharing> QUESTION 76 Which two network topologies are the most popular in switching? (Choose two.) A. BusB. Token passing busC. StarD. Extended starE. Ring Answer: CDEExplanation:http://en.wikipedia.org/wiki/Network_topology QUESTION 77 Which two VTP modes allow the creation of local VLANs? (Choose two.) A. transparentB. nativeC. serverD. clientE. on Answer: AC QUESTION 78 Which three terms are used to describe data at Layers 1, 2, and 4 of the OSI model? (Choose three.) A. PDUsB. BitsC. SequencesD. SegmentsE. PacketsF. Frames Answer: BDFExplanation: Bits - 1 layerFrames - 2 layerSegments - 4 layer

http://en.wikipedia.org/wiki/OSI_model QUESTION 79 What are two attributes of a VLAN? (Choose two.) A. A VLAN defines a collision domain.B. A VLAN defines a broadcast domain.C. Broadcasts are flooded to all VLANs.D. Collisions are flooded to all VLANs.E. A Layer 3 device is required to route packets between VLANs.F. A Layer 2 device is required to route packets between VLANs. Answer: BEExplanation: "In computer networking, a single layer-2 network may be partitioned to create multiple distinct broadcast domains, which are mutually isolated so that packets can only pass between them via one or more routers; such a domain is referred to as a virtual local area network, virtual LAN or VLAN." "A router (Layer 3 device) serves as the backbone for network traffic going across different VLANs." http://en.wikipedia.org/wiki/Virtual_LAN QUESTION 80 Which device would you select to partition a network into VLANs? A. repeaterB. bridgeC. switchD. routerE. hub Answer: C QUESTION 81 On which two components of a router can a copy of a running-configuration file be saved manually by an engineer for backup purposes? (Choose two.) A. NVRAMB. FlashC. ROMD. RAME. DRAM Answer: AB QUESTION 82 Which VTP mode disallows the creation of local VLANs? A. transparentB. tunnelingC. serverD. clientE. offF. native Answer: D Explanation: "A VTP client behaves like a VTP server and transmits and receives VTP updates on its trunks, but you cannot create, change, or delete VLANs on a VTP client. VLANs are configured on another switch in the domain that is in server mode." http://www.cisco.com/en/US/docs/switches/lan/catalyst3560/software/release/12.2_52_se/c

onfiguration/guide/swvtp.html#wp1205076 QUESTION 83 Which layer of the OSI model is associated with the reliable transmission of datagrams? A. DatagramB. RoutingC. NetworkD. Data linkE. TransportF. TransmissionG. Session Answer: EExplanation:http://en.wikipedia.org/wiki/Transport_layer QUESTION 84 Which three options describe routers compared to switches? (Choose three.) A. use IP address tables for information lookupB. concerned with packet forwardingC. operate at Layer 3 of the OSI modelD. operate at Layer 2 of the OSI modelE. use MAC address tables for information lookupF. concerned with the local delivery of frames Answer: ABC QUESTION 85 Which four statements indicate unique properties of VLAN 1 on Cisco Nexus switches? (Choose four.) A. VLAN 1 is used to flood multicast traffic.B. VLAN 1 cannot be deleted.C. VLAN 1 is used for Cisco Discovery Protocol.D. VLAN 1 is used for VTP advertisements.E. VLAN 1 defines a collision domain.F. VLAN 1 defines a broadcast domain. Answer: BCDF QUESTION 86 At which layer of the OSI model does TCP operate? A. 1B. 2C. 3D. 4E. 5 Answer: DExplanation:http://en.wikipedia.org/wiki/OSI_model QUESTION 87 Which two layers of the OSI model are combined in the Internet protocol suite network access layer? (Choose two.) A. 1B. 2C. 3D. 4E. 5F. 6G. 7 Answer: ABExplanation:http://en.wikipedia.org/wiki/Internet_protocol_suite QUESTION 88 A switch is configured to be part of a VTP domain so that its VLAN database is not affected by any changes in the domain. Which mode should be configured on this switch? A. clientB. transparentC. serverD. neutral Answer: B QUESTION 89 What action does a switch take if the destination MAC address is unknown? A. Discard frameB. Send ICMP unreachable message to sourceC. Flood packet on all portsD. Compare destination IP address against an ACL to determine if it is permittedE. Send gratuitous ARP on all ports and wait for reply before forwarding Answer: CExplanation: "What happens though when the switch receives a frame with a destination MAC address that is not included in the table? In that case the switch will just broadcast/flood the frame with the unknown destination address to all of its ports (apart from the port where the frame came from). This process is called unknown unicast flooding." <http://telconotes.wordpress.com/2013/03/09/how-a-switch-works/> !!!RECOMMEND!!! !!!RECOMMEND!!!

1.|2017 New 200-150 Exam Dumps (PDF & VCE) [106Q&As](#) Download:<http://www.Braindump2go.com/200-150.html> 2.|2017 New 200-150 Study Guide Video: YouTube Video: [YouTube.com/watch?v=ySnz1PlssKA](https://www.youtube.com/watch?v=ySnz1PlssKA)