

[2017-July-NewsValid 200-150 PDF and 200-150 VCE Free Download in Braindump2go[21-30

2017 July CCNA 200-150 Exam Dumps with PDF and VCE New Updated in www.Braindump2go.com Today! 1.|2017 New 200-150 Exam Dumps (PDF & VCE) [106Q&As](#) Download:<http://www.Braindump2go.com/200-150.html> 2.|2017 New 200-150 Exam Questions & Answers Download:

<https://drive.google.com/drive/folders/0B75b5xYLjSSNVmxoUEhTTmZZMXc?usp=sharing> QUESTION 21 Refer to the exhibit. What type of network communication is depicted? A. 802.3 frameB. TCP packetC. UDP packetD. Ethernet frame Answer: D
QUESTION 22 What is the maximum distance that is supported by Cisco passive Twinax cables? A. 5mB. 3mC. 4mD. 10m Answer: A
QUESTION 23 What two technologies can be used to connect to storage arrays on a converged Ethernet IP network? (Choose two.) A. FCoE B. Fiber ChannelC. iSCSI D. InfinBandE. FabricPath Answer: AC
QUESTION 24 Which situation will cause a switch to flood traffic out all of the ports on the switch? A. The switch receives a destination MAC address of 0000.0000.0000B. The switch receives a destination MAC address of ffff.ffff.ffffC. The switch receives a source MAC address of 0000.0000.0000D. The switch's TCAM reaches the MAC address limit.E. The switch was configured in cut-through mode. Answer: B
QUESTION 25 What layer of the OSI Model provides the logical addressing that routers use for path determination? A. transportB. networkC. applicationD. presentation Answer: B
QUESTION 26 What are three features of the IPv6 protocol? (Choose three.) A. optional IPsecB. autoconfigurationC. no broadcastsD. complicated headerE. plug-and-playF. checksums Answer: BCE
QUESTION 27 Which table in a switch must be populated with forwarding information as to reduce Layer 2 flooding in the network? A. MAC tableB. forwarding tableC. ARP tableD. routing table Answer: A
QUESTION 28 A network engineer proposes that old hubs be replaced by new Layer 2 switches in the company network. Which three are reasons for this proposal? (Choose three.) A. Each port on a switch becomes its own collision domain.B. Layer 2 switches provide IP routing at line card speed.C. Hubs create one large collision domain and one large broadcast domain, which greatly decreasing network performance.D. Switches create one large collision domain and one large broadcast domain, which greatly increases network performance.E. By connecting each device directly to a port on the hub, each port on a switch becomes its own broadcast domain.F. Data transmission is faster on switches because switches work at line card speed. Answer: ACF
QUESTION 29 To improve security, a network engineer needs to configure an access list on a router. In which mode can this list be configured? A. global configurationB. user accessC. user privilegedD. interface configuration Answer: A
QUESTION 30 What is the minimum number of disks that are needed in RAID 1? A. 4 disksB. 2 disksC. 8 disksD. 16 disks Answer: B
!!!RECOMMEND!!! 1.|2017 New 200-150 Exam Dumps (PDF & VCE) [106Q&As](#) Download:
<http://www.Braindump2go.com/200-150.html> 2.|2017 New 200-150 Study Guide Video: YouTube Video:
[YouTube.com/watch?v=ySrz1PlssKA](https://www.youtube.com/watch?v=ySrz1PlssKA)