

[2017-New-Exams100% Success-Braindump2go 7130X PDF and 7130X VCE Dumps 70q Instant Download[1-9

2017 March New Avaya 7130X Exam Dumps with PDF and VCE Released in www.Braindump2go.com **Today!**1.|NEW 7130X PDF and VCE Dumps 70Q&As Download:<http://www.braindump2go.com/7130x.html> 2.|NEW 7130X Exam Questions Download:<https://1drv.ms/f/s!AvI7wzKf6QBjgzgSs9e7vx3M6Gu>- QUESTION 1Which access control method is used by the Avaya Aura® Application Enablement Services (AES) server for administrators? A. Single Administrator simple password loginB. Challenge-Response shared-key method onlyC. System Manager AES Management MenuD. Role-Based Access Control Answer: DExplanation:Role Based Access Control (RBAC)Access to AE Services Management Console Web pages can be restricted by user authorization level. The operations that users are allowed to perform such as read, edit and delete can also be restricted.<https://downloads.avaya.com/css/P8/documents/101014052> QUESTION 2What is the process for Web browsing to the AES Management Console, and logging in with the default account and default password? A. <https://<AES> Management IP Addr>:8443, then enter login=craft password=crftpwB. <https://<AES> Management IP Addr> then enter login=admin password=admin01C. <http://<AES> Management IP Addr> then enter login=admin password=adminD. <https://<AES> Management IP Addr> then enter login=cust password=custpw Answer: DExplanation:Log in to the AE Server as the default administrator (cust).Make sure that the URL begins with "<https://>" and the host name or IP address of the AE Services Server is correct.<https://downloads.avaya.com/css/P8/documents/100171737> QUESTION 3In Avaya Aura® Communication Manager (CM) for TSAPI, which type of CTI-link needs to be configured? A. ASA1-IPB. TSAPI-IPC. ADJ-IPD. DMCC-IP Answer: CExplanation:The Avaya AES server forwards CTI requests, responses, and events between Invision CTI Server and Communication Manager. The Avaya AES server communicates with Communication Manager over an AES link. Within the AES link, CTI links may be configured to provide CTI services to CTI applications such as Invision CTI.Step 1: Enter the display system-parameters customer-options command. On Page 3, verify that Computer Telephony Adjunct Links is set to y.Step 2: Enter the add cti-link m command, where m is a number between 1 and 64, inclusive.Enter a valid Extension under the provisioned dial plan in Avaya Communication Manager, set the Type field to ADJ-IP, and assign a descriptive Name to the CTI link.Etc.

<https://www.devconnectprogram.com/fileMedia/download/edd26666-ae98-4f15-9a2a-a156d0807160> QUESTION 4Which four kinds of services does the TSAPI standard provide for third-party call control over Avaya Aura® Communication Manager (CM)? (Choose four.) A. receiving notifications of eventsB. controlling specific calls or stationsC. invoking CM featuresD. performing a remote reboot to the CM serverE. completing the routing of incoming callsF. adding new feature buttons to agent sets Answer: ABCEExplanation:A: The services in the Event Report group provide a client application with the reports of events that cause a change in the state of a call, a connection, or a device.B: The services in the call control group enable a telephony client application to control a call or connection on Communication Manager. Typical uses of these services are:placing calls from a device controlling a connection for a single call.C: The services in the query group allow a client to query device features and static attributes of a Communication Manager device.E: The services in the routing group allow Communication Manager to request and receive routing instructions for a call from a client application.<https://downloads.avaya.com/css/P8/documents/100141354> QUESTION 5Which configuration must be completed before configuring a TSAPI link on Avaya Aura® Application Enablement Services (AES)? A. A CTI link must be configured on Avaya Aura® Communication Manager (CM) first.B. A Switch Connection must be configured on Avaya Aura® Application Enablement Services (AES) first.C. A signaling-group must be configured on Avaya Aura® Communication Manager (CM) first.D. A CTI-user must be configured on Avaya Aura® Application Enablement Services (AES) first. Answer: AExplanation:If you are administering the AE Server for TSAPI, JTAPI, DMCC with Call Control, Telephony Web Service, or an AE Services integration (Microsoft or IBM Sametime), you must administer a CTI link from Communication Manager to AE Services.Follow these steps from a Communication Manager SAT to administer a CTI link type ADJ-IP.Procedure1. Type add cti-link <link number>, for example add cti-link 5.2. Complete the CTI LINK form as follows:E. In the Extension field, type <station extension>, for example 70001.F. In the Type field, type ADJ-IP.G. In the Name field, type <name of AE Server>, for example aeserver1.<https://downloads.avaya.com/css/P8/documents/100171737> QUESTION 6What are three ways of accessing Avaya Aura® Application Enablement Services (AES) to perform administration? (Choose three.) A. with an Open X.11 terminal windowB. with web accessC. with remote access using RloginD. with local access using a system consoleE. with remote access using SSH Answer: BDEExplanation:B: You can use a Web browser to access the Application Enablement Services Management Console (AE Services Management Console).DE: Administrators can access the AE Services Linux shell (command prompt) either locally using a system console or remotely using a secure shell (ssh) client. This access method applies primarily to AE Services Technicians (craft users) who perform specific tasks, such as viewing trace logs, installing

patches, and so forth.<https://downloads.avaya.com/css/P8/documents/100171737> QUESTION 7 To which other component does the Avaya Aura® Application Enablement Services (AES) Switch Connections connect? A. Avaya Aura® Media Server (AAMS) using H.323B. Avaya Aura® Session Manager (SM) using SIPC. Avaya Aura® Communications Manager (CM) using H.323D.

Avaya Aura® Communications Manager (CM) using SIP Answer: CExplanation: Adding a switch connectionThe procedure include the following steps:1. From the AE Services Management Console main menu, select Communication Manager Interface > Switch Connections.2. On the Switch Connections page, in the Add Connection field, type a switch connection name (for example Switch1)For the Secure H323 Connection check box, do one of the following: * For Communication Manager 6.3.6 or later and TLS for the H.323 Signaling Channel (normally associated with FIPS Mode), select the Secure H323 Connection check box. * For any previous release of Communication Manager without TLS for the H.323 Signaling Channel, uncheck the Secure H323 Connection check box. Etc.<https://downloads.avaya.com/css/P8/documents/100171737> QUESTION 8 What is the process for establishing a command line session to the AES Management IP Address, and logging in with the default account and default password? A. Use PuTTY to Rlogin to > AES Management IP Addr > using port 21, then enter login=admin password=admin.B. Use PuTTY to SSH to > AES Management IP Addr > using port 22, then enter login=craft password=crftpw.C. Use PuTTY to SSH to > AES Management IP Addr > using port 22, then enter login=cust password=custpw.D. Use PuTTY to SSH to > AES Management IP Addr > using port 222, then enter login=admin password=admin01. Answer: BExplanation: Use port 22, not port 21 or port 222. Log in as craft and use the default password.https://downloads.avaya.com/elmodocs2/AES/4.0/02_300356_4.pdf QUESTION 9 In which two locations is the Switch Password configured? A. In 'ip-services' form on Avaya Aura® Communication Manager (CM) and in 'TSAPI link' on Avaya Aura® Application Enablement Services (AES)B. In 'ip-services' form on Avaya Aura® Communication Manager (CM) and in 'Switch Connection' on Avaya Aura® Application Enablement Services (AES)C. In 'cti-link' form on Avaya Aura® Communication Manager (CM) and in 'Switch Connection' on Avaya Aura® Application Enablement Services (AES)D. In 'cti-link' form on Avaya Aura® Communication Manager (CM) and in 'TSAPI link' on Avaya Aura® Application Enablement Services (AES) Answer: BExplanation: Enabling AE Services refers to administering the transport link between Communication Manager and AE Services. Procedure1. Type change ip-services. Communication Manager displays the IP SERVICES form2. Complete Page 1 of the IP SERVICES form3. Complete Page 3 of the IP SERVICES form as follows.E. In the AE Services Server field, type the name of the AE Services serverF. In the Password field, create a password. This is the password that the AE Services administrator must set on the AE Server (Communication Manager Interface > Switch Connections > Edit Connection > Switch Password). The passwords must exactly match on both Communication Manager and the AE Services server.
<https://downloads.avaya.com/css/P8/documents/100171737> !!!RECOMMEND!!! 1.|NEW 7130X PDF and VCE Dumps 70Q&As Download:<http://www.braindump2go.com/7130x.html> 2.|NEW 7130X Study Guide Video: YouTube Video:
[YouTube.com/watch?v=iCsEhQEMgBY](https://www.youtube.com/watch?v=iCsEhQEMgBY)