


[2017-New-ExamsFree Offer of Braindump2go 1Y0-240 Latest Dumps with 194Q 1Y0-240 New Questions[131-140]

2017 Oct New Citrix 1Y0-240 Exam Dumps with PDF and VCE Free Updated Today! Following are some new 1Y0-240

Questions:1.[2017 New 1Y0-240 Exam Dumps (PDF & VCE) 194Q&As Download:<https://www.braindump2go.com/1y0-240.html>

2.[2017 New 1Y0-240 Exam Questions & Answers Download:

<https://drive.google.com/drive/folders/0B75b5xYLjSSNYWRSMTFQWmNPuzQ?usp=sharing>QUESTION 131Scenario: A NetScaler is configured with the following modes:* MBF* USIP* USNIP* Layer 3 modeA Citrix Administrator configured a new router and now requires some of the incoming and outgoing traffic to take different paths through the new router However, the and takes a network trace. After a short monitoring period, the administrator notices that the packets are still NOT getting to the new router from the NetScaler.Which mode should the administrator disable on the NetScaler to facilitate the addition of the new router and successfully route the packets?A. Layer 3 modeB. USIPC. MAC-based ForwardingD. USNIPAnswer: AQUESTION 132Which mode does a Citrix Administrator need to configure in order to allow the NetScaler to forward any packets that are NOT destined for an IP address that is NOT configured on NetScaler?A. USIPB. Layer 3 ModeC. Layer 2 ModeD. MBFAnswer: DQUESTION 133A Citrix Administrator has configured the commands using the command-line interface.View the screenshots (Exhibit).



```
> add rewrite action Insert_Cert insert_http_header SSL_parameter CLIENT.SSL.CLIENT_CERT.SUBJECT
Done
> add rewrite policy Insert_Cert_policy true Insert_Cert
Done
> bind lb vserver lb_vsvr_vsw -policyName Insert_Cert_policy -priority 100 -gotoPriorityExpression END -type REQUEST
Done
>
> show ssl certkey client1
www.Braindump2go.com
-----
Signature Algorithm: sha256withRSAEncryption
Issuer: C=IN, ST=KA, O=Mylab, CN=icauser@mylab.lab
Validity
Not Before: Apr 25 11:33:20 2017 GMT
Not After: Apr 25 11:42:20 2018 GMT
Subject: C=IN, ST=KA, O=Mylab, CN=icauser@mylab.lab
Public Key Algorithm: rsaEncryption
Public Key Size: 2048
Output Response Status: NONE
Done
>
```

What will be the effect of the rewrite policy, based on the exhibit?A. HTTP Header "SSL_parameter: icauser@mylab.lab" will be inserted in every RESPONSE.B. HTTP Header "SSL_parameter: icauser@mylab.lab" will be inserted in every REQUEST.C. HTTP Header "SSL_parameter: C=IN,ST=KA,O=Mylab,CN=icauser@mylab.lab" will be inserted in every RESPONSE.D. HTTP Header "SSL_parameter: C=IN,ST=KA,O=Mylab,CN=icauser@mylab.lab" will be inserted in every REQUEST.Answer: AQUESTION 134Scenario: User authentication is failing through the NetScaler. A Citrix Administrator checked the Authentication, Authorization and Auditing (AAA) policy, action and virtual server and verified that the correct configuration was in place. The administrator bypassed the NetScaler and the authentication worked.Which NetScaler utility can the administrator use to troubleshoot the access issue?A. aaad.debugB. DashboardC. nscon messageD. nslog fileAnswer: AQUESTION 135Which command should a Citrix Administrator use to configure a Content Switching virtual server for implementing the Secure Web Gateway in the transparent proxy mode?A. add cs vserver swgVS PROXY 192.168.10.1 80 -Authn401 on -authnVsName explicit-auth-vsB. add cs vserver swgVS PROXY * * -Authn401 on -authnVsName explicit-auth-vsC. add cs vserver swgVS PROXY 192.168.10.1 -Authn401 on -authnVsName transparent-auth-vsD. add cs vserver swgVS PROXY * 21 -Authn401 on -authnVsName transparent-auth-vsAnswer: CQUESTION 136In the Global Server Load Balancing (GSLB) configuration when dynamic proximity is implemented, the round trip time (RTT) between the_____and_____is measured to make the load decision. (Choose the correct option to complete the sentence.)A. IP address of the client; each of the GSLB sitesB. Local DNS of the client; each of the GSLB sitesC. Local DNS of the client; each of the GSLB servicesD. IP address of the client; each of the GSLB servicesAnswer: AQUESTION 137Scenario: A Citrix Administrator manages an environment that has a NetScaler high availability (HA) pair running on two MPX appliances. The administrator notices that the state of the Secondary NetScaler is 'Unknown' and moves the Secondary NetScaler to a new switch as a result. Also, the administrator captured a packet trace on both NetScalers. Both sent traffic on secure port 3009 and were routing back and forth to each other.What is causing the Secondary state to be 'Unknown'?A. The firewall is blocking communication between the switches.B. The administrator made both NetScalers Primary.C. The Secondary NetScaler CANNOT communicate in HA when moved to a new switch.D. The remote procedure call (RPC) nodes are NOT configured correctly.Answer: AQUESTION 138Scenario: A Citrix Administrator has configured an HTTP load-balancing virtual server with Least Response Time as the load-balancing algorithm.The administrator notices that requests to the virtual server appear to be using the Round Robin load-balancing algorithm.What could be causing the virtual server to use the Round Robin load-balancing algorithm?A. The services that are bound to the HTTP virtual server are using the PING monitor.B.

The virtual server is in startup round robin mode.C. Least Response Time CANNOT be used as a load-balancing algorithm on an HTTP virtual server.D. The NetScaler configuration has NOT been saved yet.
Answer: B
QUESTION 139
Scenario: A Citrix Administrator has configured the rewrite action as follows:
add rewrite action sync_date replace http.res.date sys.time
What is the correct way to interpret this rewrite action?
A. The rewrite action replaces the Date header in the http response with the GMT time stamp.
B. The rewrite action replaces the Date header in http response with the NetScaler system time in a conventional date format.
C. The rewrite action is invalid, as system time CANNOT be referenced in the system policy.
D. The rewrite action replaces the NetScaler system time with the Date header in a conventional date format.
Answer: C
QUESTION 140
Scenario: A Citrix Administrator manages an environment that has multiple websites running through a NetScaler MPX 5550. The NetScaler meets the needs of the environment throughout the year, except in December, when the capacity doubles. The administrator needs to handle this increased web traffic with a temporary, cost-effective solution. Which action should the administrator recommend in order to handle the increased web traffic?
A. Purchase a license to upgrade the MPX 5550 to a MPX 5650.
B. Purchase a BurstPack License.
C. Purchase Universal License.
D. Purchase NetScaler Gateway Platform License.
Answer: B

!!!RECOMMEND!!!1.[2017 New 1Y0-240 Exam Dumps (PDF & VCE) 194Q&As

Download:<https://www.braindump2go.com/1y0-240.html>2.[2017 New 1Y0-240 Study Guide Video: YouTube Video:

[YouTube.com/watch?v=IooNx0GMaHQ](https://www.youtube.com/watch?v=IooNx0GMaHQ)