

[2017-New-ExamsInstant NS0-171 VCE Dumps Free Download in Braindump2go[11-20

2017 May New Version | Network Appliance NS0-171 Exam Dumps with PDF and VCE Free Released in www.Braindump2go.com Today! 100% Real Exam Questions! 100% Exam Pass Guaranteed! 1. | 2017 New Version NS0-171 Exam Dumps (PDF & VCE) 55Q&As Download: <http://www.Braindump2go.com/ns0-171.html> 2. | 2017 New Version NS0-171 Exam Questions & Answers Download: <https://1drv.ms/f/s!AvI7wzKf6QBjghGjqrVH0dW40wYQ> QUESTION 11 Which two are the expected outputs of network interface show? (Choose two.) A. IP addresses of NAS and iSCSI logical interfaces B. iSCSI IQNs C. Namespace of SAN logical interfaces D. System WW node name E. WW port names of Fibre Channel and FCoE logical interfaces Answer: AE QUESTION 12 Which sends support summary information to NetApp through HTTPS? A. AutoSupport B. FlexSupport C. SnapSupport D. TechSupport Answer: A QUESTION 13 When configuring a volume to contain a LUN, which administrative tool automatically applies NetApp recommendations? A. Data ONTAP command-line interface B. OnCommand System Manager C. Microsoft SystemCenter D. VMware vSphere Answer: B QUESTION 14 When trying to configure a Virtual Port Channel (vPC), what might be a cause of the following error when trying to create the vPC domain? Nexus-5548-B(config)# vpc domain 10% Invalid command at " marker. Nexus-5548-B(config)# A. Have not yet turned on the vpc feature using the 'feature vpc' command B. The vPC links have to be configured before the vPC domain can be added C. The vPC domain has already been configured D. vPC domain cannot be configured at the global prompt Answer: A QUESTION 15 Which tool can be used to validate hardware installation in a FlexPod solution? A. NetApp OnCommand Insight B. NetApp Config Advisor C. NetApp OnCommand Unified Manager D. Cisco UCS Central E. Cisco UCS Director Answer: B QUESTION 16 Which policy detail should be set if you want a server to be exempt from all power capping? A. Create a Power Control Policy and set Power Capping to No Cap B. Create a Power Control Policy select cap and set the priority to 1 C. Create a Power Group with the appropriate chassis and set the Group Budget Power Cap (W) to 0 D. The UCS Power Cap feature should not be utilized in a FlexPod environment. Answer: A QUESTION 17 Which two are correct about VSAN configuration within UCS Manager? (Choose two) A. VSAN ID and FCoE VLAN ID have to match B. VSAN can be configured as fabric interconnect specific C. We can delete VSAN 1 D. VSAN IDs 3840-4079 are not available regardless of the Fabric Interconnect mode E. VSAN can be configured as a global parameter F. In addition to SAN tab, VSANs can be configured under UCSM Server tab as well Answer: BE QUESTION 18 Which two are true about Fabric Interconnect L1 and L2 ports in cluster mode? (Choose two) A. Fabric Interconnects connected via L1/L2 have to be the same model except during the upgrade B. Ports are primarily used for management traffic, but can be used for data traffic as well C. Fabric Interconnect ports L1 and L2 are 10 Gb links D. Ports can only run as a port channel E. Ports can only run as individual links F. Ports can run as a port channel or as individual links Answer: AD QUESTION 19 There are 2 chassis tied to a pair of Fabric Interconnects. First chassis, chassis-1, has 1 link between single IOM and Fabric Module. Second chassis, chassis-4, has 4 links between single IOM and Fabric Module. Chassis discovery policy is set for 2 links. Which statement is true? A. Both chassis will be added to UCS Domain utilizing all links. No additional steps needed B. Both chassis will be added to UCS Domain utilizing all links only after performing chassis acknowledgment C. Chassis-1 will not be added to UCS Domain. Chassis-4 will be added to UCS domain with all 4 links operating and no additional steps needed D. Chassis-1 will not be added to UCS Domain. Chassis-4 will be added to UCS domain with all 4 links operating after chassis acknowledgement. Answer: D QUESTION 20 With Clustered Data ONTAP, which three protocols are supported for host boot in a UCS stateless computing environment in the FlexPod configuration? (Choose three.) A. CIFS B. FCC C. FCIP D. FCoEE E. iFCPF F. iSCSIG G. NFS Answer: BDF !!!RECOMMEND!!! 1. | 2017 New Version NS0-171 Exam Dumps (PDF & VCE) 55Q&As Download: <http://www.Braindump2go.com/ns0-171.html> 2. | 2017 New Version NS0-171 Study Guide Video: YouTube Video: [YouTube.com/watch?v=NtD1KtHPUGA](https://www.youtube.com/watch?v=NtD1KtHPUGA)