

[2017-Sep.-Updated!100% Exam Pass-300-160 PDF and VCE Dumps Free from Braindump2go[89-100

2017/Sep New 300-160 Exam Dumps with PDF and VCE Free Updated Today! Following are some new 300-160 Questions:

1.|2017 New 300-160 Exam Dumps (PDF & VCE) 403Q&As Download: <https://www.braindump2go.com/300-160.html> 2.|2017 New 300-160 Exam Questions & Answers Download:
<https://drive.google.com/drive/folders/0B75b5xYLjSSNZ21HQjE0YzFwTWs?usp=sharing> QUESTION 89Which statement about FCoE is true? A. FCoE is not supported on any Nexus 2000 Series Fabric Extenders.B. Not a single FCoE VLAN can map to multiple VSANs.C. Inter-switch FCoE links can be configured to carry multiple VSANs.D. FCoE does not support NPV/NPIV mode. Answer: C QUESTION 90Which Cisco management tool provides centralized device and security policy management for Cisco VSG for Cisco Nexus 1000V Series Switches? A. Cisco UCS ManagerB. Cisco NAMC. Cisco VNMCD. Cisco DCNM Answer: C QUESTION 91Which two options are benefits of using Cisco UCS Unified Uplinks? (Choose two.) A. ability to use virtual port channelsB. optimal use of bandwidthC. fewer packets dropsD. consistent optics in Fabric InterconnectsE. no storage license required on the Fabric InterconnectsF. longer distances possible Answer: BD QUESTION 92You have designed a Cisco UCS Solution, and each Cisco UCS 6248UP Fabric Interconnect has these connections:- 4 x Cisco UCS Chassis each with 4 x 10 Gb links per Fabric- 4 x 10 Gb Unified Port Channel to the upstream Nexus switchHow many additional Fabric Interconnect port licenses are required? A. 16B. 0C. 20D. 40 Answer: A QUESTION 93Which option describes how a port is configured as a unified uplink when using Cisco UCS Manager? A. configured as an FCoE uplink portB. configured as an uplink port, then as an FCoE uplink portC. configured as an FC uplink port, then as an uplink portD. configured as an FCoE storage portE. configured as an uplink port, then as an FC uplink port Answer: B QUESTION 94You are designing a Cisco UCS Solution that uses Cisco VIC 1280 Mezzanine Adapters. Which design decision helps prevent potential bottlenecks in the system? A. Configure a NIC team, and use per VM load balancing in vCenter.B. Use the VIC 1280 in combination with the 2208XP IO Module.C. Ensure all links between the Cisco Fabric Interconnect and IO Module are configured as a port channel.D. Utilize all links between the Cisco Fabric Interconnect and IO Module.E. Configure the vNIC for an MTU of 9000. Answer: C QUESTION 95The client's data center manager has requested the physical weights of the equipment in your Cisco UCS design along with the power and cooling requirements. Where in cisco.com can you find this information? A. the product datasheetsB. the Cisco UCS power calculatorC. the Cisco UCS GUI Configuration GuideD. the Cisco UCS Hardware Installation GuideE. the Hardware and Software Interoperability Matrix Utility Tool Answer: B QUESTION 96A client has five Cisco UCS domains and is looking for the most efficient method in which to manage them. Which solution best suits this need? A. Cisco UCS DirectorB. Data Center Network ManagerC. Cisco Prime InfrastructureD. Cisco UCS CentralE. Cisco Prime Network Services Controller Answer: D QUESTION 97Which two business requirements have the most influence on the data center design? (Choose two.) A. reduce power consumptionB. increase network bandwidthC. increase storage capacityD. increase cooling requirementE. reduce virtual machine to host ratioF. reduce data center footprint (floorspace) Answer: AE QUESTION 98Your Cisco UCS design contains this hardware:- 2 x 6248UP Fabric Interconnects- 1 x 5108 Chassis containing a pair of 2204XP IO Modules- 8 x B200M3 blades, each with a VIC 1240 and no mezzanine adapterWhat is the maximum available bandwidth per fabric for each server? A. 10 GbB. 20 GbC. 40 GbD. 80 GbE. 160 Gb Answer: A QUESTION 99Which four options are important points within the Cisco UCS design? (Choose four.) A. preferred MAC address formatB. preferred guest operating systemsC. DNS configurationD. preferred WWPN formatE. service profile naming conventionsF. preferred backup strategyG. Cisco IMC IP addressing rangeH. ESX host IP addressing Answer: ADEG QUESTION 100Which command does a mainframe use for all subsequent logins for either virtual machines or logical partitions, after the initial connection and login process? A. F-Port login processB. N-Port ID VirtualizationC. FDISC login commandsD. Fibre Channel IDs Answer: C !!!RECOMMEND!!!
1.|2017 New 300-160 Exam Dumps (PDF & VCE) 403Q&As Download: <https://www.braindump2go.com/300-160.html> 2.|2017 New 300-160 Exam Questions & Answers Download: YouTube Video: [YouTube.com/watch?v=DADPr4lm2as](https://www.youtube.com/watch?v=DADPr4lm2as)