## [2018-April-New100% Success-Braindump2go 642-887 PDF Dumps 190Q Instant Download[149-159

2018 April New Cisco 642-887 Exam Dumps with PDF and VCE Free Updated Today! Following are some new 642-887 Real Exam Questions: 1.|2018 Latest 642-887 Exam Dumps (PDF & VCE) 190Q&As

Download:https://www.braindump2go.com/642-887.html2.|2018 Latest 642-887 Exam Questions & Answers Download;https://drive.google.com/drive/folders/0B75b5xYLjSSNeXNhZVlPaDA3dDA?usp=sharingQUESTION 149Which statement defines how MPLS LDT Graceful Restart works after a service interruption? A. It works independent of neighboring routers to recover MPLS forwarding informationB. It works by helping all neighboring MPLS LDP routers to recover MPLS forwarding informationC. It works by helping neighboring routers with MPLS LDP SSO/NSF and Graceful Restart to recover MPLS forwarding informationD. It works independent of neighboring non-LDP Graceful Restart routers to recover MPLS forwardinginformationAnswer: CQUESTION 150Which two factors must you consider when configuring MPLS EXP? (Choose two.)A. MPLS EXP marking is supported in the egress directionB. A packet that IP ToS classifies at ingress can be reclassified by MPLS EXP at egressC. MPLS EXP marking is supported in the ingress directionD. MPLS EXP classification for bridged MPLS packets on EVCs is supportedE. A packet that MPLS classifies at ingress can be reclassified by IP ToS at egressAnswer: CEQUESTION 151Which two options are true regarding the Pipe and Short Pipe MPLS tunneling models? (Choose two.)A. In Short Pipe mode QoS is done on the PE-to-CE link based on the customer's PHB markingsB. In Pipe mode QoS is done on the PE-to-CE link based on the service provider's PHB markingsC. In Pipe mode QoS is done on the PE-to-CE link based on the customer's PHB markingsD. In Short Pipe mode QoS is done on the PE-to-CE link based on the service provider's PHB markings E. Short Pipe mode does not need MPLS usage, but Pipe mode does Answer: ABQUESTION 152Refer to the exhibit. What is the available reservable bandwidth for P6 after successful establishment of Tunnel 1? A. 490 KbpsB. 500 KbpsC. 490 MbpsD. 500 MbpsAnswer: DQUESTION 153How is bandwidth recalculated when utilizing the automatic bandwidth adjustment feature for MPLS TE?A. The tunnel's output average is periodically sampled and then the bandwidth is adjusted to the largest sample obtained during the period, or to the configured maximumB. The tunnel's output is sampled and then the bandwidth is adjusted by a configured percentage until the configured maximum value is reachedC. Ping is used to measure congestion and the bandwidth is adjusted by a configured percentage until the maximum value is reachedD. Ping is used to measure congestion and the bandwidth is adjusted to either the minimum, average, or maximum configured bandwidth valueAnswer: AOUESTION 154Which two advantages are reasons that service providers might deploy MPLS? (Choose two.)A. to avoid using IGP in the coreB. to facilitate smooth migrations between legacy WAN technologiesC. to reduce the throughput overhead of full IPv4/IPv6 headers when traversing the coreD. to reduce the computational requirements that are placed on router CPUsE. to reduce configuration and feature requirements in the coreAnswer: CDQUESTION 155In Cisco IOS, what must be configured to ensure that an MPLS TE tunnel becomes active?A. layer 3 addressing on the tunnel, to establish bidirectional communication over the tunnelB. the tunnel for autoroute, to ensure proper installation into the forwarding planeC. a path-option configuration, for either dynamic or explicit pathsD. the tunnel with a minimum bandwidth value, to properly calculate CSPFAnswer: AQUESTION 156Which option shows how a class map is implemented that matches only packets originating from the network 10.0.0.0/8, which are not marked as VoIP Answer: BQUESTION 157An engineer is having a problem getting an operational 10 on Cisco IOS XE?A. B. C. D. Gigabit link on a Cisco ASR 9000 series router. The service provider instructs the engineer to use an LR optic. The engineer must access the router remotely. Which command should the engineer issue to determine that the correct optic has been installed? A. show controllersB. show module opticsC. show ip interfaceD. show opticsAnswer: AQUESTION 158Which message is sent through the desired LSP path by the headend router and is used to determine available resources? A. PATHB. TENTC. RSVP D. RESVAnswer: AQUESTION 159An engineer sets up QoS over MPLS networks. How many classes of traffic can one LSP support?A. as many as 8, because the EXP field is 3 bitsB. as many as 3, because the EXP field is 3 bitsC. as many as 64, because the DSCP field is 6 bitsD. as many as 6, because the DSCP field is 6 bitsAnswer: A!!!RECOMMEND!!!1.|2018 Latest 642-887 Exam Dumps (PDF & VCE) 190Q&As Download:https://www.braindump2go.com/642-887.html2.|2018 Latest 642-887 Study Guide Video: YouTube Video: YouTube.com/watch?v=LWvoUnmI3Vc