

## [2019-May-New] 352-001 Exam PDF Free Download in Braindump2go

[2019 May Braindump2go 352-001 Dumps with PDF and VCE New Updated Today!](#) Following are some new 352-001 Real Exam Questions:1.|2019 Latest 352-001 Exam Dumps (PDF & VCE) Instant

Download:<https://www.braindump2go.com/352-001.html>2.|2019 Latest 352-001 Exam Questions & Answers Instant

Download:<https://drive.google.com/drive/folders/0B75b5xYLjSSNSUNBNi1aYkpfOTQ?usp=sharing> New Question You have been hired by a startup company to provide optical services using MPLS-TP. Which three options describe reasons to use the MPLS-TP standard in your design? (Choose three.)

A. MPLS-TP is a newer packet transport technology that replaces SONET/SDH.B. MPLS-TP includes extensions to native MPLS OAM for fault detection, monitoring, and propagation.C. MPLS-TP requires a routing protocol.D. MPLS-TP uses an IANA assigned label 13 for OAM.E. MPLS-TP uses Ethernet Y.1731 OAM.

**Answer: ABD** New Question Your company plans to implement an Internet gateway router that is performing NAT. This same gateway will be terminating various IPsec tunnels to other remote sites. Which address type is appropriate for the ACL that will govern the sources of traffic entering the tunnel in the inside interface?

A. inside localB. inside globalC. outside localD. outside global

**Answer: B** New Question For a storage area network design, which technology allows a switch to support multiple Fibre Channel IDs per fabric port?

A. N-Port Identifier VirtualizationB. Inter-Virtual Storage Area Network RoutingC. ZoningD. Fabric Port TrunkingE. Node Port VirtualizationF. Expansion Port Trunking

**Answer: A** New Question A company wants to use an external appliance between its data center and WAN to optimize email and HTTP communications. The traffic flow must pass this appliance in both directions. The appliance is connected with only one interface to a Cisco IOS router and has a single IP address. Which two adjustments can you make to the network design so that the appliance is added into the traffic path? (Choose two.)

A. Configure static routes to route the traffic to the appliance.B. Adjust the dynamic routing to route the traffic to the appliance.C. Configure NAT to force the traffic to the appliance.D. Configure a route map at the data center-side interface to forward the traffic to the appliance IP address.

E. Configure a route map at the appliance-facing interface to forward the traffic to the appliance IP address.F. Configure a route map at the WAN-side interface to forward the traffic to the appliance IP address.

**Answer: DF** New Question You work for a large company that has just acquired another smaller company. You have been asked to lead a group of SAN experts from both companies to design the integration plan that will be used to interconnect the SANs and migrate the data from the newly acquired company to the main storage arrays. The first thing that the team discovers is that the two SANs have the same domain IDs. As the SAN team lead, what would you advise your team to do so that you can interconnect the two SANs while minimizing disruption?

A. Use FCIP with Write Acceleration and IVR version 1 with a transit VSAN to expedite the data transfer between the two SANs.B. Change the domain IDs on both SANs so that they are both unique and then connect ISLs between the SANs.C.

Use IVR NAT with a transit VSAN between the SANs.D. The two SANs cannot be merged without disruption.

**Answer: C** New Question Refer to the exhibit. You are designing a spanning-tree network for a small campus. Which two of these options would result in a trouble-free spanning-tree network design? (Choose two.)

A. Convert all ports to trunk ports, prune off the VLANs that you do not require, and minimize the number of blocking ports.B. Introduce Layer 3 VLANs (SVIs) and prune off the VLANs that you do not require.C. Convert all the ports to trunk and enable BackboneFast.D. Convert all the ports to trunk and enable

UplinkFast between all the links.

**Answer: AB** New Question A network designer is redesigning an enterprise campus network to ensure that Ethernet switches proactively attempt to reconnect after a fiber cut. In the design, they will have to address areas where fiber cuts exist on campus from past troubleshooting, where a single fiber is disconnected in the fiber pair, leading to looping. Which feature could be implemented in the design to allow the Spanning Tree Protocol on the switches to be protected?

A. loop guardB. UniDirectional Link DetectionC. UniDirectional Link Detection aggressive modeD. root guard

**Answer: C** New Question Refer to the exhibit. If IEEE 802.1w is in use for this network design, what are two locations where spanning-tree root can be placed to ensure the least-disruptive Layer 2 failover for clients within VLANs 3 and 4? (Choose two.)

A. Switch AB.B. Switch BC.C. Switch CD.D. Switch D

**Answer: CD** New Question A switched network is being designed to support a manufacturing factory. Due to cost constraints, fiber-based connectivity is not an option. Which design allows for a stable network when there is a risk of interference from the manufacturing hardware in use on the factory floor?

A. Design the network to include UDLD to detect unidirectional links and take them out of service.B. Design the network to include EtherChannel bundles to prevent a single-link failure from taking down a switch interconnection point.C. Design the network to include loop guard to prevent a loop in the switched network when a link has too much interference.D. Design the network to include BackboneFast on all devices to accelerate failure convergence times.

**Answer: A** New Question What are three key design principles when using a classic hierarchical network model? (Choose three.)

A. The core layer controls access to resources for security.B. The core layer should be configured with minimal complexity.C. The core layer is designed first, followed by the distribution layer and then the access layer.D. A hierarchical

network design model aids fault isolation.E. The core layer provides server access in a small campus.F. A hierarchical network design facilitates changes.

**Answer: BDF** New Question Which three techniques can be used to improve fault isolation in an enterprise network design? (Choose three.)

A. aggregate routing information on an OSPF ABR  
B. fully meshed distribution layer  
C. Equal-Cost Multipath routing  
D. EIGRP query boundaries  
E. multiple IS-IS flooding domains  
F. tuned Spanning Tree Protocol timers

**Answer: ADE** [!!!RECOMMEND!!!](#)

1.|2019 Latest 352-001 Exam Dumps (PDF & VCE) Instant Download:<https://www.braindump2go.com/352-001.html>

2.|2019 Latest 352-001 Study Guide Video Instant Download: YouTube

Video: [YouTube.com/watch?v=j82yK1lhorg](https://www.youtube.com/watch?v=j82yK1lhorg)