

[9-November-2018] Braindump2go 300-320 Brain Dumps PDF Free Download [Q470-Q486]

2018/November Braindump2go 300-320 Exam Dumps with PDF and VCE New Updated Today! Following are some new 300-320

Real Exam Questions: 1. | 2018 Latest 300-320 Exam Dumps (VCE & PDF) 553Q&As

Download: <https://www.braindump2go.com/300-320.html> 2. | 2018 Latest 300-320 Exam Questions & Answers

Download: <https://drive.google.com/drive/folders/0B75b5xYLjSSNWS1ocVZVUU03VU0?usp=sharing> QUESTION 470 An

engineer is designing an IP addressing scheme for a local company that requires multicast for its applications. For security reasons, only explicitly configured devices can be permitted to transmit across the network. Which multicast technology and address range must the engineer select? A. PIM-SM; 232.0.0.0/8 B. ASM; 232.0.0.0/8 C. SSM; 232.0.0.0/8 D. SSM; 224.0.0.0/8 **Answer: D**

QUESTION 471 An engineer is designing an infrastructure to use a 40 Gigabit link as the primary uplink and a 10 Gigabit uplink as the alternate path. Which Routing protocol allows for unequal cost load balancing? A. OSPF B. EIGRP C. ISIS D. BGP E. RIP **Answer: B**

QUESTION 472 Web server placed in front of the firewall in ACI? A. Application profile B. L4-L7 services **Answer: B**

QUESTION 473 A Consultant has been tasked with QoS design. The customer has specified that for the application end-to-end bandwidth has to be specified. With what can you accomplish this? A. IntServ with RSVP B. DiffServ C. CoS markings D. DSCP markings **Answer: A**

QUESTION 474 Which is backup WAN connected with secured connection? A. DMVPN B. GRE over IPsec **Answer: B**

QUESTION 475 Which VPN connectivity representing both Hub-and-Spokes and Spokes-to-Spokes? A. DMVPN B. IPsec VPN C. VPN Router D. VPN hub **Answer: A**

QUESTION 476 A network Engineer is designing a hierarchical design and needs to optimize WAN design. On what group of devices can a network engineer summarize routes to remote WAN sites? A. Core B. Distribution C. Data Center Distribution WAN Edge D. WAN Edge E. Campus access distribution layer **Answer: B**

QUESTION 477 EIGRP configured on access switch level. What needs to be taken into account for optimal results? A. Configure stub networks B. configuring switch-to-switch C. carry multiple VLANs D. fixed-configuration switches **Answer: A**

QUESTION 478 There's a requirement to separate networks within an organization. What technology can be used while preserving hardware? A. Virtual Context B. VRF **Answer: A**

QUESTION 479 Which technology you will use to connect 2x Data Centres and extend Layer 2 VLANs? (Choose two) A. OTV B. VXLAN C. Fabric Path D. IS-IS **Answer: AB**

QUESTION 480 While designing a wide area network, the network team wants to avoid undesired transit traffic through remote branch sites with multiple WAN connections. Which option can be used to manage traffic flows in the remote network? A. route weighting B. route tagging C. route filtering D. route leaking **Answer: C**

QUESTION 481 What are the True regarding 802.1X. (Choose three) A. Authenticates the user itself B. Authenticates the device itself C. If the device does not support, allow the access automatically D. Cisco proprietary E. Industry standard **Answer: ABE**

QUESTION 482 Cisco FabricPath brings the benefits of routing protocols to Layer 2 network Ethernet environments. What are two advantages of using Cisco FabricPath technology? (Choose two) A. Cisco FabricPath relies on OSPF to support Layer 2 forwarding between switches, which allows load balancing between redundant paths. B. Cisco FabricPath provides MAC address scalability with conversational learning. C. Loop mitigation is provided by the TTL field in the frame. D. Cisco FabricPath is IETF-standard and is not used with Cisco products. E. Cisco FabricPath technology is supported in all Cisco platforms and can replace legacy Ethernet in all campus networks. **Answer: BC**

QUESTION 483 A client request includes a network design that ensures all connections between the access layer and distribution layer are active and forwarding traffic at all times. Which design approach achieves this request? A. Enable backbone fast on the two distribution switches and create a port channel between each access layer switch and both distribution switches B. Configure HSRP for all VLANs and adjust the hello timer for faster convergence C. Configure Rapid PVST+ and adjust the timers for fast convergence D. Create a VSS between the two distribution switches and also create a MEC between the VSS and each access layer switch. **Answer: D**

QUESTION 484 What is the most important consideration when selecting a VPN termination device? A. CPU cycles per second B. VPN sessions per interface C. Packets per second D. Bits per second **Answer: C**

QUESTION 485 Which option is a design recommendation for route summarizations? A. Filtered redistribution for the prevention of re-advertising of routes B. Routing protocol stub areas C. Route summarization for scalable routing and addressing design D. Defensive route filtering to defence against inappropriate routing traffic E. Route summarization to support greater volumes of transit traffic **Answer: B**

QUESTION 486 A network engineer wants to limit the EIGRP query scope to avoid high CPU and memory utilization on low-end routers as well as limiting the possibility of a stuck-in-active routing event between HQ and branch offices. Which way to achieve these goals? A. Configure different Autonomous System number per each branch office and HQ and redistribute routes between autonomous systems. B. Configure all routers at branch offices as EIGRP stub and allow only directly connected networks at branch offices to be advertised to HQ. C. Configure all routers at branch offices as EIGRP stub D. Configure all routers at HQ and branch offices as

EIGRP stub
Answer: C!!!RECOMMEND!!!1. | 2018 Latest 300-320 Exam Dumps (VCE & PDF) 553Q&As
Download: <https://www.braindump2go.com/300-320.html> | 2018 Latest 300-320 Study Guide Video: YouTube Video:
[YouTube.com/watch?v=cTXMNZdiRI](https://www.youtube.com/watch?v=cTXMNZdiRI)