## [March-2018-NewBraindump2go 352-001 PDF Dumps 510Q Free Offer[128-138

2018 March New Cisco 352-001 Exam Dumps with PDF and VCE Free Updated Today! Following are some new 352-001 Real Exam Questions: 1.|2018 Latest 352-001 Exam Dumps (PDF & VCE) 510Q&As

Download:https://www.braindump2go.com/352-001.html 2.|2018 Latest 352-001 Exam Questions & Answers Download:https://drive.google.com/drive/folders/0B75b5xYLjSSNSUNBNi1aYkpfOTO?usp=sharingQUESTION 128Which two OSPF design considerations should you implement to support the eventual growth of a network, so that CPU and memory are unaffected by the size and complexity of the link-state database in a large service provider network? (Choose two.)A. Turn on route dampening.B. Create network summaries.C. Turn on the Incremental SPF feature.D. Add more memory.E. Turn on packet pacing.F. Add redundancy between critical locations. Answer: CEQUESTION 129ACME Corporation is deploying a new HR application that requires the network infrastructure to monitor and react to certain conditions in the network. Which feature should be used to meet this design requirement? A. Cisco IOS Embedded Event Manager B. IP SLAC. reflexive ACLsD. route mapsE. SOAPF. exit statusAnswer: AQUESTION 130Refer to the exhibit. How would you redesign the network to improve availability of the routers 1A and 1B at the core site? A. Enable Graceful Restart Helper for OSPFB. Use link bundles over multiple slotsC. Use APS Ethernet circuits and redundant interfacesD. Create a multichassis system with the two routersAnswer: DQUESTION 131Your company is designing a service provider network management solution in which customers are billed for 95th percentile network utilization. The service provider requires that an IETF standard be utilized to collect the data. Which method should be used to collect the data?A. IPFIXB. NETFLOWC. RMOND. IPFLOWE. NBARAnswer: AQUESTION 132You are creating a network design that will influence the traffic path across the MPLS core on a virtual private LAN. Which parameter is included in your design to manage the traffic?A. Deploy MPLS traffic engineering and modify the path using the preferred path.B. Deploy MPLS traffic engineering and modify the path using auto-route, static routing, or PBR.C. Create an MPLS traffic engineering tunnel and modify the path using a static route.D. Create an MPLS traffic engineering tunnel and modify the path using auto-route announce. Answer: AQUESTION 133Your company needs to baseline web traffic on a per-session basis for network application reporting. Which two mechanisms, when combined, fulfill the requirement? (Choose two.)A. Flexible NetflowB. Remote MonitoringC. Cisco IOS IP Service Level AgreementD. Class-Based Quality of Service Management Information BaseE. Network-Based Application RecognitionAnswer: AEQUESTION 134AS100 and AS200 each have two peering points in different parts of their network. AS100 would like to use one of the links and keep the other link as backup. What should be changed for the design inside AS100 for prefixes received from AS200?A. MEDB. weightC. AS-PATHD. local preferenceAnswer: DQUESTION 135You are designing a traffic monitoring and analysis system for a customer. Which traffic monitoring technique would you recommend to place the least amount of burden on the network infrastructure? A. SPAN monitor ports B. NetFlow C. IP NBARD. passive taps Answer: DQUESTION 136Your company requires two diverse multihop External Border Gateway Protocol peerings to a partner network. Which two methods would you use to improve lost peer detection? (Choose two.)A. Use Bidirectional Forwarding Detection for the peers.B. Use Selective Address Tracking and match the peers.C. Use subsecond keepalives for the peers.D. Use subsecond hold timers for the peers.E. Use Fast Peering Session Deactivation for the peers.F. Use subsecond minimum route advertisement Interval timers for the peers. Answer: BEQUESTION 137A designer is working with a large bank to redesign their network. The designer wants to minimize complaints regarding slow application response times across the WAN. It is suspected that currently traffic is not being classified and marked correctly somewhere in the network. Which tool should the designer recommend to validate quality of service mappings and use?A. SNMPB. IPFIXC. IP SLAD. protocol analyzerE. NBARAnswer: BQUESTION 138A network design includes a long signaling delay in notifying the Layer 3 control plane that an interface has failed. Which two of these actions would reduce that delay? (Choose two.)A. Enable lower data link layer recovery systems to have an opportunity to restore the interface.B. Increase the notification of interface flaps.C. Reduce the time for the network to reconverge.D. Increase network stability. Answer: AD!!!RECOMMEND!!!1.|2018 Latest 352-001 Exam Dumps (PDF & VCE) 510Q&As Download:https://www.braindump2go.com/352-001.html 2.|2018 Latest 352-001 Study Guide Video: YouTube Video: YouTube.com/watch?v=CcH0sE7s21E