

## [March-2018-NewDownload Braindump2go 400-051 VCE Dumps 542Q Free[242-252

2018 March New Cisco 400-051 Exam Dumps with PDF and VCE Free Updated Today! Following are some new 400-051 Real Exam Questions:1.|2018 Latest 400-051 Exam Dumps (PDF & VCE) 542Q&As Download:

<https://www.braindump2go.com/400-051.html>2.|2018 Latest 400-051 Exam Questions & Answers Download:

<https://drive.google.com/drive/folders/0B75b5xYLjSSNWGttdXZ3UGRqWjQ?usp=sharing>QUESTION 242Which statement about using the Answer File Generator to load a Cisco Unified Communications virtual machine is true?A. You must copy the output text to a file named platformConfig.txt.B. Each host should be copied to its own configuration file.C. The answer file can be used only when performing the new identity process to load the Cisco Unified Communications virtual machines.D. The configuration file should be placed inside an ISO file and mounted on the virtual machine.Answer: BQUESTION 243What is the maximum number of option 150 IP addresses that a Cisco IP SCCP phone will accept and use from a DHCP server?A. 1B. 2C. 3D. 4E. 5Answer: BQUESTION 244What is the maximum number of option 66 IP addresses that a Cisco IP SCCP phone will accept and use from a DHCP server?A. 1B. 2C. 3D. 4E. 5Answer: AQUESTION 245Which two statements about BFCP with Cisco Unified Communications Manager are true? (Choose two.)A. BFCP is supported only on full SIP networks.B. Cisco Unified Communications Manager allows BFCP only over UDP.C. BFCP is not supported for third-party endpoints.D. BFCP is not supported through Cisco Unified Border Element.E. BFCP is supported between Cisco Unified Communications Manager and a TelePresence MCU.Answer: ABQUESTION 246Which two statements about the restrictions for support of H.239 are true? (Choose two.)A. SIP to H323 video calls using H.239 are not supported.B. Redundancy for H.323 calls is not supported.C. H.239 calls are not supported over intercluster trunks with Cisco Unified Communications Manager.D. H.239 is not supported with third-party endpoints.E. Cisco Unified Communications Manager supports a maximum of three video channels when using H.239.Answer: ABQUESTION 247Which method does a Cisco Unified 9971 phone use to send keep-alive messages to Cisco Unified Communications Manager?A. SIP NOTIFY with Event set to keep-aliveB. SIP OPTIONS C. SIP REGISTER with Expires set to zeroD. SCCP StationRegisterE. SCCP StationServerReqAnswer: CQUESTION 248Refer to the exhibit. Which user agent has the recipient role in this SIP REFER call transfer? A. user agent AB. user agent BC. user agent CD. user agent B and CE. user agent A and BAnswer: BQUESTION 249In a SIP REFER-based call transfer, which SIP message is being used by the recipient to notify the originator that the final recipient was successfully contacted?A. 200 OKB. NOTIFY with a message body of 200 OKC. 202 AcceptedD. 100 TryingE. 200 BYEAnswer: BQUESTION 250When the Cisco Unified Communications Manager service parameter "Auto Call Pickup Enabled" is selected, which two softkeys on an IP phone connect you to an incoming call? (Choose two.)A. PickupB. GpickupC. CallBackD. SelectE. JoinAnswer: ABQUESTION 251Which three requirements must be met to share Enhanced Location Based Call Admission Control bandwidth usage between clusters? (Choose three.)A. The Cisco Unified Communications Manager version must be 8.6 or higher.B. The location name must be the same on both clusters.C. SIP ICT must use the Shadow location.D. The Location Bandwidth Manager Service should be started on only two servers in each cluster.E. A Location Bandwidth Manager Hub Group must be created for each cluster.F. Links must be created to the Shadow location.Answer: BCEQUESTION 252Refer to the exhibit. The exhibit shows an outgoing SIP 401 response message from Cisco Unified Communications Manager to a SIP VoIP service provider gateway. Which action can the Cisco Unified Communications Manager systems administrator use to change the response to "200 OK"? A. Make sure the gateway IP address of the SIP VoIP service provider is defined correctly in Cisco Unified Communications Manager SIP trunk.B. Enable OPTIONS ping on Cisco Unified Communications Manager SIP trunk.C. Disable OPTIONS ping on Cisco Unified Communications Manager SIP trunk.D. Create an SIP response alias to force outgoing 401 messages to "200 OK".E. Disable digest authentication on Cisco Unified Communications Manager SIP trunk.Answer: E!!!RECOMMEND!!!1.|2018 Latest 400-051 Exam Dumps (PDF & VCE) 542Q&As Download:<https://www.braindump2go.com/400-051.html>2.|2018 Latest 400-051 Study Guide Video: YouTube Video: [YouTube.com/watch?v=Ish6if\\_c\\_JY](https://www.youtube.com/watch?v=Ish6if_c_JY)