

## [May-2019-NewBraindump2go 300-075 Exam PDF and VCE Free Download

[2019/May Braindump2go Cisco CCNP Collaboration CIPTV2 300-075 Dumps with PDF and VCE New Updated Today!](#)

Following are some new 300-075 Exam Questions:1.|2019 Latest 300-075 Exam Dumps (PDF & VCE) Instant

Download:<https://www.braindump2go.com/300-075.html>2.|2019 Latest 300-075 Exam Questions & Answers Instant

Download:<https://drive.google.com/drive/folders/0B75b5xYLjSSNOXRpM1hydUpDU3M?usp=sharing>New QuestionHow long is the default keepalive period for SRST in Cisco IOS?A. 45 secB. 30 secC. 60 secD. 120 sec**Answer: B**New QuestionWhich option is a valid test scenario to verify that Cisco Unified Communications Manager failover works and endpoints register with the backup call manager?A. During a predetermined maintenance window, stop the Cisco IP Phone Services service on the primary Unified CM. Devices should reregister with the backup Unified CM in the Cisco CallManager Group.B. During a predetermined maintenance window, stop the Unified CM service on the Publisher.Devices should reregister with the backup Publisher in the Cisco CallManager Group.C. During a predetermined maintenance window, stop the TFTP service on the primary call manager. Devices should reregister with the backup Unified CM in the Cisco CallManager Group.D. During a predetermined maintenance window, stop the Unified CM service on the primary call manager. Devices should reregister with the backup Unified CM in the CallManager Group.

**Answer: D**New QuestionWhich three commands can be used to verify SRST fallback mode? (Choose three.)A. show telephony-service allB. show telephony-service ephone-dnC. show telephony-service ephoneD. show telephony-service voice-portE. show telephony-service tftp-bindings**Answer: ABC**New QuestionCompany X has a Cisco Unified Communications Manager cluster and a Cisco Unity Connection cluster at its head office and implemented SRST for its branch offices. One Monday at 2:00 pm, the WAN connection to a branch office failed and stayed down for 45 minutes. That day the help desk received several calls from the branch saying their voicemail was not working but they were able to make and receive calls.Why did the users not realize the WAN was down and prevented access to their voicemail?A. All the phones should have started ringing the instant the WAN connection failed to signal the start of SRST mode.B. All calls should have dropped when the WAN failed so users would be instantly aware.C. Although the phones were still working, the users should have noticed that the phone displays said "SRST Fallback Active".D. The voice administrators at the head office did not call the users to notify them.**Answer: C**New QuestionWhat are two important considerations when implementing TEHO to reduce long-distance cost? (Choose two.)A. on-net calling patternsB. E911 callingC. number of route patternsD. caller ID**Answer: BD**New QuestionWhich two statements about the use of the Intercluster Lookup Service in a multicluster environment are true? (Choose two.)A. Cisco Unified Communications Manager uses the ILS to support intercluster URI dialing.B. ILS contains an optional directory URI replication feature that allows the clusters in an ILS network to replicate their directory URIs to the other clusters in the ILS network.C. Directory URI replication does not need to be enabled individually for each cluster.D. To enable URI replication in a cluster, check the Exchange Directory URIs with Remote Clusters check box that appears in the SIP trunk configuration menu.E. If the ILS and directory URI replication feature is disabled on a cluster, this cluster still accepts ILS advertisements and directory URIs from other neighbor clusters; it just does not advertise its local directory URIs.

**Answer: AB**New QuestionIn Cisco Unified Communications Manager, where do you configure the +E.164 number that is advertised globally via ILS?A. ILS configuration under Advanced FeaturesB. +E.164 alternate number under Directory Number SettingsC. Device Information under Phone ConfigurationD. Route Pattern under Route/Hunt  
**Answer: B**New QuestionWhen implementing a dial plan for multisite deployments, what must be present for SRST to work successfully?A. dial peers that address all sites in the multisite clusterB. translation patterns that apply to the local PSTN for each gatewayC. incoming and outgoing COR listsD. configuration of the gateway as an MGCP gateway**Answer: B**New QuestionWhich code snippet is required for SAF to be initialized?A. Service FamilyB. External-ClientC. router eigrpD. topology base  
**Answer: C**New QuestionWhen using SAF, how do you prevent multiple nodes in a cluster from showing up in the Show Advance section of the SAF Forwarder configuration?A. Configure the publisher node only in the SAF Forwarder configuration page.B. Append an @ symbol at the end of the client label value in the SAF Forwarder configuration page.C. Configure the correct node in the EIGRP configuration of the gateway router that is associated with the Cisco Unified Communications Manager node.D. Configure the SAF Security Profile Configuration to support only a single node.**Answer: B**New QuestionWhich statement about the SAF Client Control is correct?A. The SAF Client Control is a configurable inherent component of Cisco Unified Communications Manager.B. The SAF Client Control is a non-configurable inherent component of Cisco Unified Communications Manager.C. The SAF Client Control is a non-configurable inherent component of the Cisco IOS Routers.D. The SAF Client Control is a configurable inherent component of the Cisco IOS Routers.**Answer: B**!!!RECOMMEND!!!1.|2019 Latest 300-075 Exam Dumps (PDF & VCE) Instant Download:<https://www.braindump2go.com/300-075.html>2.|2019 Latest 300-075 Study Guide Video Instant Download: YouTube Video: [YouTube.com/watch?v=S2wMYKmSgoc](https://www.youtube.com/watch?v=S2wMYKmSgoc)