

[November-2018200-310 Dumps PDF Free Offered By Braindump2go for Downloading[Q168-Q178

2018/November Braindump2go 200-310 Exam Dumps with PDF and VCE New Updated Today! Following are some new 200-310 Real Exam Questions:1.|2018 Latest 200-310 Exam Dumps (PDF & VCE) 551Q&As

Download:<https://www.braindump2go.com/200-310.html>2.|2018 Latest 200-310 Exam Questions & Answers

Download:<https://drive.google.com/drive/folders/0B75b5xYLjSSNbNsWnFEczRBdU0?usp=sharing>QUESTION 168What type of topology supports WAN redundancy when a balance is required between cost, high availability, and performance?A. partial meshedB. full meshedC. starD. ringE. hub-and-spokeF. bus G. point-to-point

Answer: AQUESTION 169What is the key limitation of using Internet circuits as a backup to a private enterprise WAN?A. circuit bandwidthB. prioritizationC. securityD. operational expense

Answer: BQUESTION 170A network design engineer is seeking a dynamic routing protocol that supports fast convergence in a Cisco environment. What protocol allows for this?A. EIGRPB. OSPFC. RIPD. BGPE. IS-IS

Answer: AQUESTION 171What are two benefits of the bottom-up design approach? (Choose two.)A. allows a quick response to a design requestB. facilitates design that is based on previous experienceC. requires little or no notation of actual organizational requirements for implementationD. incorporates organizational requirementsE. provides a broader overview to the organization and the designer

Answer: ABQUESTION 172Which network layer is the best fit for security features such as DAI and DHCP snooping?A. campus coreB. enterprise edgeC. campus distributionD. remote-access VPNE. enterprise data centerF. campus access

Answer: FQUESTION 173Directory services and electronic messaging are performed at which layer of the network?A. coreB. applicationC. distributionD. network

Answer: BQUESTION 174Refer to the exhibit. Which configuration can be used to implement FHRP protocol and load balancing at the same time? A. R1Interface Ethernet0ip address 171.16.6.5 255.255.255.0 standby 1 preempt standby 1 ip 171.16.6.100 standby 1 track Serial0 standby 2 preempt standby 2 ip 171.16.6.200 standby 2 track serial 0 standby 2 priority 95!!R2interface Ethernet0ip address 171.16.6.6 255.255.255.0 standby 1 preempt standby 1 ip 171.16.6.100 standby 1 track Serial0 standby 1 priority 95!!R2interface Ethernet0ip address 171.16.6.6 255.255.255.0 standby 1 preempt standby 1 ip 171.16.6.200 standby 2 track serial 0 standby 2 priority 95!!R2interface Ethernet0ip address 171.16.6.6 255.255.255.0 standby 1 preempt standby 1 ip 171.16.6.100 standby 1 track Serial0 standby 1 priority 95C. R1Interface Ethernet0ip address 171.16.6.5 255.255.255.0 standby 1 preempt standby 1 ip 171.16.6.100 standby 1 track Serial0 standby 1 priority 95standby 2 preempt standby 2 ip 171.16.6.200 standby 2 track serial 0B. R1Interface Ethernet0ip address 171.16.6.5 255.255.255.0 standby 1 preempt standby 1 ip 171.16.6.100 standby 1 track Serial0 standby 1 priority 95!!R2interface Ethernet0ip address 171.16.6.6 255.255.255.0 standby 1 preempt standby 1 ip 171.16.6.200 standby 2 track serial 0 standby 2 priority 95!!R2interface Ethernet0ip address 171.16.6.6 255.255.255.0 standby 1 preempt standby 1 ip 171.16.6.100 standby 1 track Serial0 standby 1 priority 95

Answer: AQUESTION 175Cisco FabricPath brings the benefits of routing protocols to Layer 2 network Ethernet environments. What are two advantages of using Cisco FabricPath technology? (Choose two.)A. Cisco FabricPath provides MAC address scalability with conversational learning.B. Loop mitigation is provided by the TTL field in the frame.C. Cisco FabricPath technology is supported in all Cisco platforms and can replace legacy Ethernet in all campus networks.D. Cisco FabricPath relies on OSPF to support Layer 2

forwarding between switches, which allows load balancing between redundant paths.E. Cisco FabricPath is IETF-standard and is not used with Cisco products.

Answer: ABQUESTION 176A network design shows two routers that are directly connected to an Ethernet switch using optical connections. There is an OSPF adjacency between the routers. In this design, which solution ensures that interface-down detection is reported as quickly as possible to the IGP?A. optimized OSPF SPF timersB. Bidirectional

Forwarding DetectionC. automatic protection switchingD. optimized OSPF LSA timersE. Ethernet OAM CFM monitoring

Answer: BQUESTION 177Which statement is true about using a DNS server to discover a controller IP?A. The AP sends a discovery request to the first controller on the list and then goes down the list chronologically until it receives a discovery response.

B. The AP sends a discovery request to the last controller on the list and then goes up the list chronologically until it receives a discovery response.C. The AP sends a discovery request to all controllers on the list simultaneously.D. Multiple controller IP

addresses in a DNS response are not supported.

Answer: CQUESTION 178Refer to the exhibit. A network engineer at a technical call center receives a call from a customer complaining that only 56 kbps of data can be transferred over the T1 Frame Relay WAN circuit at a remote site. The engineer checks the Frame Relay switch and confirms that only 56 kbps is being transferred over the circuit. The engineer requests the router configuration of the customer headquarters site router. What is causing this issue to occur?

A. The wrong CIR is configured.B. The BECN configuration is causing this issue.C. The class name is spelled wrong under the interface.D. The wrong DLCI number is assigned to the interface.

Answer: C!!!RECOMMEND!!!1.|2018 Latest 200-310

Exam Dumps (PDF & VCE) 551Q&As Download:<https://www.braindump2go.com/200-310.html2>.|2018 Latest 200-310 Study Guide Video: YouTube Video: [YouTube.com/watch?v=Qrsw1ousUGM](https://www.youtube.com/watch?v=Qrsw1ousUGM)