# [Oct.-2016-NEWBraindump2go 400-101 PDF Dumps and 400-101 VCE Dumps Free Offered[1205-1208

2016/10/14 New 400-101: CCIE Routing and Switching Written Exam, v5.1 Exam Questions Updated Today!Free Instant Download 400-101 Exam Dumps (PDF & VCE) 1219q from Braindump2go.com Today! 100% Real Exam Questions! 100% Exam Pass Guaranteed! 1.|2016/10 New 400-101 Exam Dumps (PDF & VCE) 1219q Download: http://www.braindump2go.com/400-101.html2.|2016/10 New 400-101 Exam Questions and Answers: https://1drv.ms/b/s!AvI7wzKf6QBjbxAXh0ll7uNwWIk  QUESTION 1203What is the source MAC address of a BPDU frame that is sent out of a port ? A.    A the lowest MAC address on the switchB.    the higest MAC address on the switchC.    the MAC address of the individual port that is sending the BPDUD.    the same as the MAC address in the brigdge ID Answer: C QUESTION 1204 Which type of ACL can be applied only to Layer 2 pods? A.    port ACLsB.    reflexive ACLsC.    reflexive ACLsD.    dynamic ACLsE.    VLAN ACLs Answer: A QUESTION 1205Refer to the exhibit. Which two statements about this topology are true? (Choose two) A.    Destination 192.168.23.0/24 is unable to use interface Fa0/1 as the LFA.B.    Interface FastEthernet 0/1 is the primary path to destination 192 168.23.0/24.C.    The FastEthernet 0/0 and FastEthernet 0/1 interfaces are used as LFA for destination 192.168.23.0/24D.    Only interface FastEthernet 0/1 are used as the LFA for destination 19216823.0/24.E.    Interface FastEthernet 0/0 is the primary path to destination 192.168.23.0/24.F.    Only FastEthernet 0/0 is used as the LFA to destination 192.168.23.0/24. Answer: AE QUESTION 1206Which three options are the main security features in SNMPv3? (Choose three) A. authenticationB.    MIB persistenceC.    message integrityD.    authorizationE.    encryptionF.    accounting Answer: ACE QUESTION 1207Which two are best practices when configuring VLAN and switch port ?(Choose two) A.    Assign an unused VLAN to all unsed portsB.    Always use MST to ensure a loop-free topology.C.    Use a dedicated native VLAN ID for all trunk port&D.    Use VLAN1 as the network management VLANE.    Set the default port status to Enable. Answer: AC QUESTION 1208 Which command can you enter to disable logging for terminal lines? A.    no logging tropB.    no logging monitorC.    no logging bufferD.    no logging consoleE.    no logging count Answer: B   !!!RECOMMEND!!!  1.Braindump2go|2016/10 New 400-101 Exam Dumps (PDF & VCE) 1219q Download: http://www.braindump2go.com/400-101.html2.Braindump2go|2016/10 New 400-101 Exam Questions and Answers:  https://1drv.ms/b/s!AvI7wzKf6QBjbxAXh0ll7uNwWIk