

[New 300-460 Dumps] Real 300-460 PDF Free Download from Braindump2go [45-55]

2018/August Braindump2go New 300-460 Exam Dumps with PDF and VCE Free Updated Today! Following are some new 300-460 Real Exam Questions:1.[2018 Latest 300-460 Exam Dumps (PDF & VCE) 112Q&As

Download:<https://www.braindump2go.com/300-460.html>2.[2018 Latest 300-460 Exam Questions & Answers

Download:<https://drive.google.com/drive/folders/0B75b5xYLjSSNQWptMkpOdDQ0b28?usp=sharing>QUESTION 45An

administrator is installing a hypervisor and has provisioned a dedicated LAN connectivity, set the boot order, and is now rebooting the server to start installation. Which method is the administrator using to install the hypervisor?A. host image mappingB. KVM consoleC. PXE installationD. virtual boot

Answer: CQUESTION 46Which option describes the purpose of system VLANs as used in a Cisco Nexus 1000V Switches?A. is the equivalent of 802.1q tagging in the Cisco Nexus 1000VB. enables interface connectivity before an interface is programmed via the control planeC. allows the VSM to send opaque data to all hosts under managementD. supplements pVLAN functionality in a virtualized environment

Answer: CQUESTION 47Which option lists the steps to configure a Cisco UCS B-Series server for jumbo frames and the Cisco Discovery Protocol?A. On the Servers tab, set CDP enabled under the vNIC interface.Set the vHBA MTU to 9000.Assign the network control policy to the vHBA.B. On the Servers tab, create a network control policy with CDP enabled.On the vNIC select the jumbo-frame checkbox.Assign the network control policy to the vNIC.C. On the LAN tab, create a network control policy with CDP enabled.Create a vNIC with an MTU of 9000.Assign the network control policy to the vNIC.D. On the LAN tab, create a vHBA template with an MTU of 9216.Select the CDP checkbox.Assign the network control policy to the vHBA.

Answer: DQUESTION 48During which process are Cisco UCS UUID, MAC, and WWPN identifiers allocated from the pool?A. service profile instantiationB. server boot timeC. service profile assignment to a serverD. service profile template creation

Answer: CQUESTION 49Which port-channel type is the best when deploying a Cisco Nexus 1000V with Cisco UCS B-Series Blades?A. channel-group mode on sub-group cdpB. channel-group auto mode on mac-pinningC. channel-group auto mode activeD. channel-group mode on mac-pinning

Answer: B
Explanation:

http://www.cisco.com/c/en/us/products/collateral/switches/nexus-1000v-switch-vmware-vsphere/white_paper_c11-558242.htmlQUESTION 50A Cisco UCS Director administrator is configuring vHBA. Which four fields are needed to configure vHBA? (Choose four.)A. vHBA NameB. Adapter PolicyC. Template TypeD. OrganizationsE. DescriptionF. Fabric IDG. UCS Organization NameH. UCS Account Name

Answer: ACEFQUESTION 51Which two statements describe Ethernet and vEthernet port profiles? (Choose two.)A. Ethernet port profiles may only be assigned to Cisco UCS unified ports when configured as type link.B. Ethernet port profiles are assigned to physical interfaces such as vmnics. vEthernet port profiles are assigned to virtual interfaces such as vNIC, vmk, or VTEP.C. An MTU change is required on the Ethernet port profiles to support jumbo frames.D. vEthernet port profiles are assigned to physical interfaces such as vmnics. Ethernet port profiles are assigned to virtual interfaces such as vNIC, vmk, or VTEP.

Answer: BCQUESTION 52Which option describes the function of an initiator in Storage Area Networking?A. stats a connection over the fabric to one or more portsB. provides a network infrastructure consisting of one or more Fibre Channel switchesC. creates a connection over the fabric to one or more initiator portsD. an endpoint that receives data in the SAN infrastructure

Answer: DQUESTION 53Which option describes the difference between in-band and out-of-band IP management pool in Cisco UCS?A. An out-of-band network is the only method to connect with the Cisco IMC blade.B. An in-band network policy requires twice the IP address space of an out-of-band policy.C. An out-of-band network is reachable over the Fabric Interconnect server interfaces, and in-band network is reachable over uplink interfaces.D. An out-of-band network is reachable over the Fabric Interconnect mgmt0 interfaces, and in-band network is reachable over uplink interfaces.

Answer: DQUESTION 54Which four fields are needed when creating a WWPN pool in Cisco UCS Director? (Choose four)A. the first and last WWPN address in the blockB. the number of WWPN addresses in the blockC. a unique name for the initiatorD. the first WWPN address in the blockE. the WWN for the initiatorF. a unique name for the poolG. the last WWPN address in the blockH. a description for the pool

Answer: ABFHQUESTION 55The Cisco UCS usNIC feature improves performance of software applications by bypassing the kernel network stack. Which option lists the steps to configure usNIC capable vNIC in the correct order?A. Create a usNIC connection policy, create a vNIC, set vNIC connection policy to usNIC, and install the usNIC RPM driverB. Modify the vNIC network control policy to usNIC, modify usNIC Ethernet adapter policy, and install the usNIC RPM driverC. Create a usNIC connection policy, create a vNIC, set vNIC adapter policy to Linux, and install the usNIC RPM driverD. Create a vNIC, modify usNIC Ethernet adapter policy, set vNIC connection policy to usNIC, and install the usNIC RPM driver

Answer: D
Explanation:

http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/gui/config/guide/2-2/b_UCSM_GUI_Configuration_Guide_2_2/configuring_network_related_policies.pdf!!!RECOMMEND!!!1.|2018 Latest 300-460 Exam Dumps (PDF & VCE) 112Q&As
Download:<https://www.braindump2go.com/300-460.html>2.|2018 Latest 300-460 Study Guide Video: YouTube Video:
[YouTube.com/watch?v=dGmdw4715x8](https://www.youtube.com/watch?v=dGmdw4715x8)